PRESTO® DIAL GAUGE TESTING REPORT

| Owner Name | Owner Contact | Date |
|--|---|---|
| Type of Pressure Canner: | | |
| Testing Unit #81288 is used only wit Honor and Presto ® units. DO NOT US customer support with questions https://youtu.be/wVR98tzqXBc | E with All American, Mirro, or ot | |
| Condition of Dial Gauge – select o | <u>ne</u> * | |
| ☐ Good ☐ Rusty ☐ Brok *REPLACE gauge if any box other | | oisture Too scratched to read |
| Condition of Lid Components – se Vent Pipe ☐ Good/Clear | | |
| Gasket Good NOTE: Gasket should be stored (d | \Box Cracked/Drry) in base of the canner betw | • |
| Over-Pressure Plug Goo NOTE: Over-pressure plug should | | |
| Handles ☐ Good *REPLACE or repair components a | ☐ Cracked/M as necessary. | issing |
| Accuracy of Dial Gauge: Master gauge registers: | <u>6 psi</u> <u>11 psi</u> | <u>15 psi</u> |
| Your gauge registers: | | |
| Recommendation (√ check one): ☐ Canner is in good shape and d | ial gauge is accurate . Canner | may be used 'as is.' |
| modification to processing pro Dial gauge reads up to 2 difference from the re gauge reads 10 psi, you food will be safe if proce Dial gauge reads up to difference and process | essure (see above) (X select of 2 pounds lower than the Massquired pressure. If the MASS may process at 10 psi when the essed at the gauge pressure.) 2 pounds higher than the N | ster gauge. You may subtract the TER gauge reads 11 psi and your e instructions say 11 psi. (Optional; Master gauge. You must add the e MASTER gauge reads 11 psi and |
| ☐ Dial gauge reads more than 2 should be replaced . Contact P | - | |
| ☐ Canner lid and dial gauge are i | in poor condition and the uni | t should not be used. |